



Preferred Specifications

Document Number	Issue Date	Rev. Date
F-2855	07/18	03/21

200-100-ECL

Modular Slide-In CAFSystem

200-100-ECL shall be a slide-in, modular, portable compressed air foam unit designed and constructed to discharge water, foam solution or compressed air foam. The system develops of 200 GPM of water at 150 PSIG (800L/min @ 10 bar) and 100 CFM of air at 125 PSIG (1.13 m³/min @ 8.6 bar). The 200-100-ECL develops 200 GPM and 100 CFM @ 125 PSI (800 l/min and 2.83 m³/min @ 8.6 bar) simultaneously. The 200-100-ECL shall also feature compressed air for pneumatic tools. The unit shall come with a Rand 100 sCFM compressor, Aquis™ foam proportioner, Tellurus Digital Control System and two (2) 1.5" Foamulators.

This unit shall come with a CPD-2 centrifugal water pump utilizing an aluminum case, double-hubbed bronze impeller, stainless steel shaft and maintenance-free mechanical seal. It shall come with a 3-inch NPT intake and 2-inch NPT discharge. It shall come with a Venturi Primer with electric activation switch and a poly chain drive transmission with an automatic tensioner and 8mm pitch sprockets.

The system shall contain two (2) 1.5-inch Foamulators using an independent pressure regulation, keeping constant mixing pressure in the mixing chamber. This pressure regulation allows a variation of the pump discharge pressure above the minimum working pressure without disrupting the function of the system or changing the consistency of the extinguishing agent.

The system shall be powered by a Kohler engine, model KDI2504TCR, four-cylinder, liquid-cooled, delivering a maximum of 74 horsepower (55 kW), four-cycle, diesel fueled. The engine shall come with a three (3) year manufacturer's warranty. The engine shall draw fuel from a fuel tank (not supplied) via a pulse fuel pump. There shall be a pressure lube system with spin-on oil filter. An extension hose is installed on the engine oil drain with a valve located at the oil pan and a plug installed in the end of the hose to facilitate oil changes. It shall come with a 12 or 24-volt electric with 80A alternator, electric ignition and start switch along with a spark arrestor muffler.

The frame of the unit shall be made of high-strength, steel.

The system shall come with an oil-filled, rotary screw air compressor, sized to supply a minimum of 100 scfm (2.83 m³/min) of usable air. The system shall utilize a spin-on, full-flow oil filter unit control oil flow to the cooler. All lines are routed in braided hose conforming to SAE 100R1 standards for hydraulic hose. The system shall be available with a modular air / oil separator and an air compressor cooling system. The air compressor shall be cooled by a 12 or 24V electric / air fan type cooler, maintaining recommended operating temperatures throughout the full operational range in ambient temperatures up to 115°F (46.1° C).

The unit shall come with a spin-on, full-flow oil filter unit is part of the system to control oil flow to the cooler. All lines are routed in braided hose conforming to SAE 100R1 standards for hydraulic hose. The unit shall be available with a modular air / oil separator. The unit shall be available with an air compressor cooling system. The air compressor shall be cooled by a 12 or 24 V electric / air fan type cooler. The system maintains recommended operating temperatures throughout the full operational range in ambient temperatures up to 115°F (46.1° C)

All air hoses, fittings and piping with the unit are rated to a minimum of 250 psi (17.5 bar). Air line fittings are constructed of brass, bronze or steel. Stainless steel or brass check air valves are utilized at all air injection points to prevent water back flow into the air lines. All hoses shall be secured to the frame with insulating clamps and located away from any heat sources.

The systems inlet plumbing inlet piping shall be 3-inch with 2.5-inch tank to pump stainless steel pipe with 2.5-inch overboard suction.

The systems discharge shall have plumbing to two panel mounted 1.5-inch discharge water/foam.CAFS outlets and one panel mounted 1.5-inch water only outlet M-NST incorporate a stainless steel manifold, welded stainless steel pipe. All discharge plumbing is designed and tested to a minimum of 500 psig (34.5 bar) burst pressure.

The unit shall come with panel mounted drain valves are provided to drain water from the water pump, discharge manifold and compressor colder.

The system shall come with an Aquis™ foam proportioner with Tellurus Digital Control System which shall allow for one-button operation and engage the entire system, pump module with electric motor/motor driver and microcontroller unit, foam concentrate strainer, shielded electrical cables for connection for all electronic components, foam inject check valve, WYE strainer and flowmeter and tee.

The unit shall be available with optional items:

- Top and side enclosures
- 1.5" discharge for front turret
- On-Site delivery instruction – contact factory for pricing
- Threads on panel intake and discharges HN/NST, NPSH, BSP or STORZ
- 1" discharge w/panel control, water/foam

The unit shall come standard with a seven-year limited warranty.