

**Pump Features**

- High-tensile gray iron body
- Bronze replaceable wear rings for increased pump life
- Bronze, mechanically and hydraulically balanced eliminates vibration
- Stainless steel impeller shaft
- Mechanical Seal (self-adjusting)
- 5-inch Victaulic Intake (CZ Model)
- 6-inch Victaulic Intake (CZU Model)
- 4-inch ANSI flange Discharge (CZ Model)
- 4-inch Victaulic Discharge (CZU Model)
- Direct drive with 1.97-10 spline for Spicer 3-4-3051 end yoke.
- Horizontal or vertical discharge position
- Bearing housing bracket position – Inverted or Vertical

Warranty

Waterous Seven-Year Limited Warranty

Conditions of Sales

For details on Waterous Condition of Sales, refer to F-2190, *Conditions of Sales* located on the Waterous web site at www.waterousco.com or by contacting Waterous.

CZ / CZU Pump Performance

Model	FLOW			PRESSURE			
	GPM	l/min	l/sec	PSI	bar	kPa	MPa
CZ	950	3600	60	260	18	1800	1.8
CZU	1500	5678	94.6	250	17	1700	1.7

Optional Equipment

- VENTURIS™ Air Priming System, see F-2940
- Electric Priming System (Rotary Vane), see F-2418
- Pressure Control Systems:
 - Discharge Relief Valve, see F-897
 - Piloted Intake Relief Valve, see F-2192
 - Non-Piloted Intake Relief Valve, see F-2192-N
- Corrosion Protection – Zinc Intake Screens and Magnesium Anodes
- Overheat Protection Manager, F-2422
- Drain Valves, see F-1158
- Discharge Valves, see F-1161
- Optional Intake Side Mounting Bracket Position – Inverted or Vertical

Industry Leading Sales and Support

When you purchase equipment, not only do you get quality products, you get quality service. Our expert service technicians are the best in the business and they are always happy to answer any service questions you might have.

Sales/Applications Assistance

Phone: 651-450-5234 (Press 3)
pumpsales@waterousco.com

Service Assistance

Phone: 651-450-5200
Fax: 800-488-1228
service@waterousco.com