



# PB18-2515 SERIES

## PORTABLE PUMPS



### PB18-2515 Pump Performance

	FLOW			PRESSURE			
	GPM	l/min	l/sec	PSI	bar	kPa	MPa
<b>Max Flow</b>	150	567	9.45	90	6.5	650	.650
<b>Max Pressure</b>	75	284	4.73	135	9	900	0.9

### Pump Specifications:

**Type:** Combination  
**Intake:** 2-1/2-inch female NPT

**Discharge:** Ball valve with 1-1/2-inch male NH thread (2515B)  
 Ball valve with 1-1/2-inch female NPT (2515B)  
 1-1/2-inch female NPT (2515F) (No Ball Valve)

#### Volute Body and Head:

High-strength aluminum alloy, anodized for superior corrosion resistance.

#### Impeller:

High-strength, corrosion-resistant bronze, fully-enclosed, double-hubbed to balance hydraulic thrust, mechanically balanced to eliminate vibration.

#### Wear Rings:

Long wearing bronze. Easy to replace when required to restore original pump efficiency.

#### Shaft Sleeve:

High-strength stainless steel.

#### Shaft Seal:

Spring loaded mechanical type.

### Optional Components

#### Operator's Panel:

Operator's panel includes discharge pressure gauge, compound intake pressure gauge, start and stop control, speed control and panel light.

#### Exhaust Primer:

Combination spark arresting muffler and exhaust primer, fast and easy to use. Quarter-turn bronze priming valve, operates with push/pull knob.

#### Rail Base:

Rigid steel channels. Control panel and fuel tank shipped loose.

#### No Base:

Control panel and fuel tank shipped loose.

#### Wrap-Around Base

Tubular steel design to protect pump and engine from roll over damage. Mast light available as an option. **NOTE: Models with Wrap-Around Bases are CE Marked.**

### Warranty

Waterous Two-Year Limited Warranty

### Conditions of Sales

For details on Waterous Condition of Sales, refer to F-2190, *Conditions of Sales* located on the Waterous web site at [www.waterousco.com](http://www.waterousco.com) or by contacting Waterous.

### Dimensions:

Base Type	Length (in/cm)	Width (in/cm)	Height (in/cm)	Dry Weight (lb/kg)	Ship Weight (lb/kg)
Rail	19-1/4 (48.9)	19-1/2 (49.5)	24.5 (62.2)	111 (50.5)	148 (67.3)
Wrap-Around	31 (78.7)	20-1/2 (52.1)	26 (66.04)	133 (50.5)	161 (73.2)
No Base	19 (48.3)	19-1/2 (49.5)	23.5 (59.7)	106 (48)	143 (64.9)

### Engine Specifications:

#### Engine:

Briggs & Stratton, model 356447, Vanguard V-Twin air cooled, overhead valve (OHV) design delivers a maximum output of 18 HP (13.4 kW) @ 3600 RPM. 34.75 cu. in. (570 cc) displacement, 4-cycle, gasoline fueled, horizontal shaft.

#### Lubrication:

Full pressure lubrication system with an automotive style oil filter. Oil fill tube with dipstick.

#### Starter:

12-volt electric and manual recoil.

#### Alternator:

16 A

### Fuel Tank:

6.95 quart (6.58 L) top mounted tank

### Maximum Full Throttle Performance

