APPLICATIONS AVAILABLE

WE HAVE MANY DIFFERENT CONFIGURATIONS AVAILABLE FOR YOUR APPLICATION NEEDS AND ARE WILLING TO WORK WITH YOU TO MEET YOUR NEEDS.










CONTACT A WATEROUS SALES
REPRESENTATIVE TODAY BY
CALLING 651-450-5000 OR
EMAIL US AT
INFO@WATEROUSCO.COM

125 HARDMAN AVE S South St Paul, MN 55075

WATEROUSCO.COM



WATEROUS AQUIS™ ULTRAFLOW

Waterous AQUIS™ ULTRAFLOW is a high-capacity demand based concentrate foam proportioning system available in 160/300/500 GPM configurations. ULTRAFLOW is compatible with all current AFFF and non-fluorinated concentrates. UltraFlow utilizes an electronic closed loop measurement through the use of magnetic meters, and the control of the concentrate injection rate relative to water flow provides precise concentrate solution to sixteen (16) independent discharges.

ULTRAFLOW SYSTEM COMPONENTS:

- One (1) Tellurus Touchscreen HMI
- One (1) Primary System Control Module
- One (1) Hydraulic Pump
- One (1) Hydraulic Motor
- One (1) Hydraulic Oil Cooler with Temperature Controller
- One (1) Hydraulic Reservoir with Filtering System
- One (1) Foam Concentrate Pump (160, 300 or 500 GPM)
- One (1) Concentrate Pump Discharge Pressure Transducer
- Discharge Line Assembly (DLA)
 - Magnetic Flowmeters
 - Ratio Control Valves
 - Check Valves
 - Paddle Wheel Flowmeters

OEM SUPPLIED COMPONENTS:

- Hydraulic Hoses and Couplings
- Hydraulic Pressure Gauge
- Hydraulic Temperature Gauge
- Concentrate Hoses and Piping





AIR PRIMER



MANUAL OVERRIDE





UP TO 16)

