



Data Sheet

Form No. DS-4020	Issue Date 06/15/17	Rev. Date 1/31/23
----------------------------	-------------------------------	-----------------------------

Waterous Eclipse GEN 2.0 CAFS As used with CM and CS Series Fire Pumps

Available as follows:

Drive	CAFS			Pump and Transmission		
	Model	Air (CFM)	Water (U.S. GPM)	Pump		Transmission Model
				Model	Material	
Belt off Back of Pump Transmission <i>(Direct Drive)</i>	150-ECL	150	300	CM, CMU, CS, CSU	Iron	C22B, C22C, C22D, C22E, C22F

Specify a CAF System as follows:

Voltage:

12 or 24

Model:

150-ECL

Sump:

Vertical *(Standard)*

Tee *(Optional)*

Oil Cooler Strainer:

In-Line *(Standard)*

Panel Mounted *(Optional)*

The Following Items are Optional:

Hose and Fitting Kit:

(Provides Hoses and Fittings to connect Compressor, Sump, Separator Filter and Oil Cooler)

Without *(Standard)*

With *(Optional)*

Oil Inlet Check Valve:

(Required when Sump is installed 12 in. or more above Compressor Rotor centerline, retains oil in compressor)

Without *(Standard)*

With *(Optional)*

Foam Generators:

See Data Sheet DS-4024

Foam Pump:

See Data Sheet DS-4014