Issued: 5/91 Revised: 03/12/01

## WATEROUS

WATEROUS COMPANY

SOUTH ST. PAUL, MINNESOTA

## 2-1/2 FULL FLOW DISCHARGE VALVE ASSEMBLY

REF NO.	DESCRIPTION	REF NO.	DESCRIPTION
GV8 GV9 GV10 GV15 GV16 GV23 GV24 GV28 GV31 GV32 GV36 GV37	Seal spring or wave spring Seal Valve ball Upper stem bushing Lower stem bushing (Part of GV31) Valve cover Mounting flange Tapped flange Valve body subassembly (includes GV16) Seal retainer Flat socket hd cap screw, zinc pld, 7/16–14 x 3/4 in. Hex hd bolt, 7/16–20 x 1–1/2 in. Cap screw, 7/16–20 x 1–1/8 in. (used instead of bolt GV37 when discharge flange has tapped mounting	GV49 GV54 GV56 GV60 GV64 GV66 GV67 GV69 GV74 GV86 GV95 GV96	O-ring packing Sq socket pipe plug, 3/4 in. Flat socket hd cap screw, zinc pld, 3/8–16 x 5/8 in. Discharge adapter (See note) Pipe nipple, 2–1/2 x 10 in. (See note) Hose nipple (See note) Control arm Socket hd cap screw, 1/4–20 x 3/8 in. Spirol pin, SS, 3/16 x 1–1/2 in. Hex socket pipe plug, 1/4 in. Plain washer, 1/4 in. Lock washer, 7/16 in. Repair kit, (consists of GV8, GV9, GV42, GV43, GV45, GV46, GV47 and GV49) Valve and operator subassembly (flange mounted valve
GV38 GV42 GV43 GV45 GV46 GV47	noles) Hex nut, 7/16–20 D-ring packing D-ring packing D-ring packing D-ring packing D-ring packing D-ring packing		only – does not include the following parts: GV24, GV37, GV38 and GV47)  Note: This part may have been furnished by either Waterous Company or original equipment manufacturer.

PLEASE NOTE

