



SPECIFICATIONS – AIR COMPRESSOR MODULES: 250-150-P Performance Enhancing Integrated Pump/Compressor Systems

PTO-driven, integrated water pump / air compressor designed specifically for installation in fire apparatus. 250-150-P develops a minimum of 250 GPM of water at 125 PSIG (473 L/min @ 8.6 bar) and 150 CFM of air at 125 PSIG (4.25 m³/min @ 8.6 bar) simultaneously. The 250-150-P is also backed by an industry exclusive five-year warranty.

Other Available Models: 250-100-P: Equipped with a Waterous CPK-2 pump, the 250-100-P is capable of developing a minimum of 200 GPM of water at 125 psig (757 l/min @ 8.6 bar) and 100 cfm at 125 psig (2.8 m³/min @ 8.6 bar) simultaneously.



Pump Specifications:

Waterous CPK-2 centrifugal fire pump. CPK-2 utilizes a high-tensile gray iron body, bronze impeller, replaceable wear rings and maintenance-free mechanical seals.

Intake and Discharge:

3 inch intake, 2 inch discharge

Pressure Relief:

An optional pressure relief system is available to comply with NFPA 1906 standards.

Priming System (Optional):

Waterous VPOS Oil-free primer. Rotating parts in the VPOS are made of corrosion-resistant, anodized aluminum, stainless steel and composite materials.

Panel Mounted Instruments:

The following items and controls are provided for installation on the pump operator's panel:

- Air compressor PTO engagement switch (OEM provided)
- AutoSync compressor controls w/engraved instruction plate
- Air compressor oil temp. gauge w/warning light and alarm
- CAF system air pressure gauge
- Air flow meter (optional)
- An air valve for each compressed air foam discharge.

Air Compressor Specifications:

The air compressor is an oil-flooded, rotary screw type, sized to supply a minimum of 150 scfm (4.2 m³/min) of usable air.

Pneumatic Modulating Inlet Valve:

The air compressor is controlled by the pneumatic modulation inlet valve mounted on the air end. The pneumatic modulation inlet valve controls air delivery while maintaining constant pressure.

Auto Sync Balancing System:

Automatically maintains the air pressure within +/- 5% of the water pump pressure throughout the pressure range. The Auto Sync Balancing System is located on the operator's panel and allows for the following modes:

- Automatic - Air pressure matched to water pressure
- Fixed - Air pressure defaults to manual setting on compressor mounted control valve.
- Unload - Air pressure reduced to 40 psig (2.8 bar) for standby operations
- Run - Air compressor in run operation. Air pressure determined by Auto or Fixed setting.

Air Compressor Oil System:

A spin-on, full-flow oil filter unit and a thermostatic valve are all part of the system to control oil flow to the cooler. All lines are routed in braided hose conforming to SAE 100R1 standards for hydraulic hose.

Modular Air/Oil Separator:

Replacement elements for the oil filter and separator are available.

Air Compressor Cooling System:

The air compressor is cooled by the unit's water pump, utilizing a copper and brass shell and tube heat exchanger. When the fire pump is operating, water flows through the heat exchanger while an in-line removable strainer, on the water inlet side, prevents clogging. The system maintains recommended operating temperatures throughout the full operational range in ambient temperatures up to 115°F (46.1° C).

Air Compressor Transmission:

Poly Chain drive with an manual tensioner and 8mm pitch sprockets.

Foam Systems (Optional):

- Aquis™ Foam Proportioner with operator interface terminal (OIT), pump module with electric motor/motor driver and microcontroller unit, foam concentrate strainer, shielded electrical cables for connection of all electronic components, foam inject check valve, WYE Strainer and flowmeter and tee.

Industry-Leading Sales and Support

When you purchase Waterous equipment, not only do you get quality products, you get quality service. Our expert service technicians are the best in the business and they are always happy to answer any service questions you might have.

Sales/Applications Assistance

Phone: 651-450-5234 (Press 3)
pumpsales@waterousco.com

Service Assistance

Phone: 651-450-5200
Fax: 800-488-1228
service@waterousco.com